FLOOR STRIPPER CLP

Page: 1

Compilation date: 24/11/2008

Revision date: 15/03/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FLOOR STRIPPER CLP

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: R & D PRODUCTS

3 & 4 VICTORIA MILLS

WESTGATE

CLECKHEATON

WEST YORKSHIRE

BD19 5DR

UNITED KINGDOM

Tel: 01274 851516

Fax: 01274 851516

Email: admin@rd-products.co.uk

1.4. Emergency telephone number

Emergency tel: 07921885509

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P260: Do not breathe mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

FLOOR STRIPPER CLP

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

RM ALCOHOL ETHOXYLATE 9 CLP

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	68439-45-2	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%

RM DO NOT USE CLP

205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	1-10%
			Acute Tox. 4: H302; Skin Corr. 1B:	
			H314	

RM TETRAKAL CLP

	230-785-7	7320-34-5	-	Eye Irrit. 2: H319	1-10%
--	-----------	-----------	---	--------------------	-------

RM BUTYL GLYCOL CLP - REACH registered number(s): 01-2119475108-36

203-905-0	111-76-2	-	Acute Tox. 4: H302; Skin Irrit. 2: H315;	1-10%
			Eye Irrit. 2: H319; Acute Tox. 4: H312;	
			Acute Tox. 4: H332	

Section 4: First aid measures

4.1. Description of first aid measures

running weter for 10 minutes or langer if substance is still on skin. Obtain medical	
running water for 10 minutes or longer if substance is still on skin. Obtain medical	
attention if irritation persists	
Eye contact: Bathe the eye with running water for 15 minutes. Seek medical advice if irritation	
persists	
Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10	
minutes. If patient feels unwell seek medical attention	
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If irritation is	
experienced, mouth and throat may be rinsed with water. Get medical advice if irritation	
continues.	

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

FLOOR STRIPPER CLP

Eye contact:	There may be irritation and pain. The eyes may water profusely. The vision may become
	blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Corrosive burns may appear around the lips.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into rain water drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

FLOOR STRIPPER CLP

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Original packaging

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

RM DO NOT USE CLP

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2.5 mg/m3	7.6 mg/m3	-	-

Respirable dust

RM BUTYL GLYCOL CLP

UK 25ppm 50ppm	-	-
----------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.
Respiratory protection: Non required in well ventilated areas
Hand protection: Impermeable gloves.
Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liq	uid
--------	-----	-----

Colour: Colourless

Solubility in water: Miscible in all proportions

Viscosity: Non-viscous

pH: 12

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

FLOOR STRIPPER CLP

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Hot surfaces.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

RM DO NOT USE CLP

IVN	RAT	LD50	225	mg/kg
ORL	MUS	LD50	700	mg/kg
ORL	RAT	LD50	1720	mg/kg
SCU	RAT	LD50	1500	mg/kg

RM TETRAKAL CLP

DERMAL	RBT	LD50	>2000	mg/kg
DUST/MIST	RAT	1H LC50	>1.1	mg/l
ORAL	RAT	LD50	>2000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain. The eyes may water profusely. The vision may become

blurred. May cause permanent damage.

FLOOR STRIPPER CLP

Ingestion: There may be soreness and redness of the mouth and throat. Corrosive burns may appear around the lips.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

(Non hazardous for transport)

14.3. Transport hazard class(es)

Transport class: 8

FLOOR STRIPPER CLP

Page: 7

Marine pollutant: No

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.